

# CAP-Phase

Universal Tester



## Combined phase comparator and voltage detector

Universal Tester for voltage detection, phase comparison and phase sequence test at capacitive HR- and LRM interfaces according to IEC 61243-5.

## No battery required

Self-powered microprocessor technology

## Phase sequence indication

## Maintenance test

For capacitive HR or LRM interfaces

## Integrated self test

Covering Universal Tester and test leads.

## Scope of supply

Universal-Tester,  
two test leads (length 2 m),  
two HR/LRM adaptors,  
carrying case



CAP-LINE

# CAP-Phase

Universal Tester

## Accessories

### Padded shoulder bag

Part number: 2500650



### Test lead set 2 x 4,5 m

Part number: 2500344



### Universal adapter cable set

Adapter cables for bushings with not standardized distances of interfaces

Part number: 2500063



### Test lead 20 cm

Short test lead for easy handling in case of voltage detection and interface testing

Part number: 2500356



## Technical data

Applied standard:	IEC 61243-5 (voltage detecting and phase comparison)
Classification of phase comparator according to standard:	UPC
Dimensions Universal Tester:	l x w x d = 170 x 80 x 35 mm

Test leads:	2 x 2 m
Dimensions carrying case:	l x w x d = 275 x 340 x 83 mm
Auxiliary voltage:	not required
Protection class:	IP 54
Operating temperature:	-25°C to +55°C
Storage temperature:	-30°C to +70°C
Part number:	2500062

Kries - Energietechnik GmbH & Co KG

Sandwiesenstr. 19  
D-71334 Waiblingen  
www.kries.com

Telefon +49 7151 96932 - 0  
Telefax +49 7151 96932-16  
E - Mail service@kries.com

KRIES -   
ENERGIETECHNIK