



Dimension drawing BXT BAS

Basic circuit diagram with and without plugged  
-in module

- **4-pole device and for universal use with all types of surge arrester modules**
- **Plugging and removing of the surge arrester modules without signal interruption**
- **Universal design without protective components**

BLITZDUCTOR XT base part, very space-saving universal feed-through terminal for supporting SPD modules without signal interruption. The SPD module is safely earthed by the supporting foot of the DIN rail by means of a snap-in fixing device. As no components of the protective circuit are situated in the base part, maintenance work is only required for the protection modules.

BXT BAS	
Operating temperature range	-40°C...+80°C
Degree of protection	IP 20
Mounting on	35 mm DIN rail acc. to EN 60715
Connection input / output	screw / screw
Cross-sectional area, solid	0.08 - 4 mm <sup>2</sup>
Cross-sectional area, flexible	0.08 - 2.5 mm <sup>2</sup>
Tightening torque (terminals)	0.4 Nm
Earthing by	35 mm DIN rail acc. to EN 60715
Enclosure material	polyamide PA 6.6
Colour	yellow
<b>Ordering information</b>	
Type	BXT BAS
Part No.	<b>920 300</b>
Packing unit	1 pcs.

Change in form and technology, with masses, weights and materials we reserve ourselves in the sense of the progress of the technology. The illustrations are noncommittal.