

SAFETY EQUIPMENT

Accessories for DEHNcap/A Voltage Indicator

VOLTAGE DETECTING SYSTEMS

HR-LRM Test Adapter

For electrical and mechanical adaptation of HR (HO) systems to LRM systems.

Used as a measuring impedance with $X_C = 36$ megohms for maintenance tests of HR coupling units (with suitable μ A meter).

Type	Dimensions	Distance between plugs	Distance between sockets	Part No.
MA DCA HR LRM	85 x 50 x 30 mm	19 mm	14 mm	767 133



LR-LRM Test Adapter

For mechanical adaptation of LR (NO) systems to LRM systems

Type	Dimensions	Distance between plugs	Distance between sockets	Part No.
MA DCA LR LRM	105 x 50 x 30 mm	jack 6.3 mm	14 mm	767 136



Plastic Case, empty

With foam padding

Type	Colour	Dimensions	Part No.
KKL 26 22 5	●	265 x 225 x 50 mm	767 106



Plastic Case, empty

With foam padding

Max. capacity:

- 1 DEHNcap/PC
- 2 DEHNcap/A or IT
- 2 Test adapters
- 2 DEHNcap/P
- 1 DEHNcap/P test unit

Type	Colour	Dimensions	Part No.
KKL DCA	●	395 x 295 x 105 mm	767 107

