

## SAFETY EQUIPMENT

## Accessories for DEHNcap/PC-LRM Phase Comparator

## VOLTAGE DETECTING SYSTEMS

**HR-LRM Test Adapter**

For electrical and mechanical adaptation of HR (HO) systems to LRM systems.

Used as a measuring impedance with  $X_C = 36$  megohms for maintenance tests of HR coupling units (with suitable  $\mu$ A meter).

Type	Dimensions	Distance between plugs	Distance between sockets	Part No.
MA DCA HR LRM	85 x 50 x 30 mm	19 mm	14 mm	767 133

**LR-LRM Test Adapter**

For mechanical adaptation of LR (NO) systems to LRM systems

Type	Dimensions	Distance between plugs	Distance between sockets	Part No.
MA DCA LR LRM	105 x 50 x 30 mm	jack 6.3 mm	14 mm	767 136

**Plastic Case, empty**

With foam padding

Max. capacity:

- 1 DEHNcap/PC
- 2 DEHNcap/A or IT
- 2 Test adapters
- 2 DEHNcap/P
- 1 DEHNcap/P test unit

Type	Colour	Dimensions	Part No.
KKL DCA	●	395 x 295 x 105 mm	767 107

**Artificial Leather Bag, empty**

With shoulder strap

Type	Colour	Dimensions	Part No.
KLT 23 16 4	●	235 x 160 x 40 mm	767 500

