

INFO

2 component pliers

Industrial quality

HAUPA divides the VDE pliers assortment into three groups.

1. 2C VDE pliers with plug-on handles
2. VDE pliers, coating-insulated, treated with a 2-coloured coating-isolation (outside red/inside yellow)
3. VDE pliers with a 2-coloured coating-isolation (outside red/inside yellow), working head insulated

These pliers fulfil the VDE standard 1000 V IEC 60900:2004

Combination pliers DIN 5244 VDE

german pattern, comfort grip, alloyed carbon steel, C 45, oil-hardened, cutting edges induction hardened, for soft and hard wire up to 150 kp/mm² (N 1500), polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 12 00	185	350	1
21 12 02	205	400	1

Side cutters DIN 5238 B VDE

swedish pattern, high alloyed carbon steel, oil-hardened, C 60, cutting edges induction hardened, for soft and hard wire up to 200 kp/mm² (N 2000), polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	CC-Ø	weight	PU
21 12 04	165	3	250	1
21 12 06	185	3,5	320	1

Heavy duty side cutters DIN 5238 A VDE

C 60, cutting edges induction hardened, polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	CC-Ø	weight	PU
21 12 17	170	2,5	230	1
21 12 19	205	3,0	285	1

Wire stripping pliers DIN 5232 VDE

C 45, oil-hardened, with spring and adjustment screw, for cable of 0,2 - 6 mm Ø, polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 12 14	160	240	1

VDE pliers, sheathed handles

Long chain nose pliers DIN 5236 A VDE

alloyed carbon steel, C 45, oil-hardened, cutting edges induction hardened, for any wire up to 150 kp/mm² (N 1500), polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 12 08	200	straight	260
21 12 10	200	45° angled nose	260

Short flat nose pliers DIN 5258 VDE

C 45, oil-hardened, polished chrome plated, short body, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 12 12	160	250	1

Short round nose pliers DIN 5257 VDE

C 45, alloyed carbon steel, oil-hardened, polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 12 16	160	250	1

Water pump pliers VDE

C 45, alloyed carbon steel, oil-hardened, polished chrome plated, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 12 21	240	330	1

Cable cutter VDE

C 45, alloyed carbon steel, oil-hardened, bronzed, sheathed handles



▲ 1000 V IEC 60900:2004



Art. No.	length	Ø	weight	PU
21 12 23	200	14 mm	310	1

VDE-pliers, 2-coloured coating-insulation

Combination pliers DIN 5244 VDE

alloyed carbon steel, C 45, oil-hardened, cutting edges induction hardened, for soft and hard wire up to 150 kp/mm² (N 1500), german pattern, polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 00 56	185	350	6
21 00 58	205	400	6

Side cutters DIN 5238 B VDE

swedish pattern, high alloyed carbon steel, oil-hardened, C 60, cutting edges induction hardened, for soft and hard wire up to 200 kp/mm² (N 2000), polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	CC-Ø	weight	PU
21 01 00	165	3	260	6
21 01 02	185	3,5	360	6

Heavy duty side cutters DIN 5238 B VDE

swedish pattern, high alloyed carbon steel, oil-hardened, C 60, cutting edges induction hardened, for soft and hard wire up to 200 kp/mm² (N 2000), polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	CC-Ø	weight	PU
21 01 17	180	2,7	350	6
21 01 19	200	3,0	400	6
21 01 10	240	3,5	500	6

Front cutters VDE

alloyed carbon steel, cutting edges induction hardened, polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red

▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 03 03	160	350	6

Long chain nose pliers DIN 5236 A VDE

alloyed carbon steel, C 45, oil-hardened, cutting edges induction hardened, for any wire up to 150 kp/mm² (N 1500), polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 03 88	200	straight	260
21 03 90	200	45° angled nose	260

Short round nose pliers DIN 5257 VDE

C 45, alloyed carbon steel, oil-hardened, polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 02 96	160	250	6

Short flat nose pliers DIN 5258 VDE

C 45, alloyed carbon steel, oil-hardened, polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 02 70	160	250	6

Wire stripping pliers DIN 5232 VDE

C 45, oil-hardened, with spring and adjustment screw, for cable of 0,2 - 6 mm Ø, polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



▲ 1000 V IEC 60900:2004



Art. No.	length	weight	PU
21 06 48	160	240	6

2 components pliers set VDE, sheathed handles

with VDE-safety-isolation, best quality, pliers polished chrome plated, 4-pieces.

- Combination pliers 185 mm
- Side cutter 165 mm
- Long chain nose pliers 200 mm
- Wire stripping pliers 160 mm



▲ 1000 V IEC 60900:2004

Art. No.	set	weight	PU
22 01 23	4-pieces	780	1

Pliers set, 2-coloured coating-insulation

C 45, oil-hardened, 2-coloured coating-insulation - inside yellow/ outside red. Pliers polished chrome plated, 4-pieces.

- Combination pliers 185 mm
- Diagonal cutters 165 mm
- Long chain nose pliers, straight 200 mm
- Wire stripping pliers 160 mm



▲ 1000 V IEC 60900:2004

Art. No.	set	weight	PU
22 01 26	4-pieces	750	1

haupa

...convincing solutions

Water pump pliers

heavy pattern, made of chrome vanadium steel, with roll, polished chrome plated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 05 88	260	580	6

Water pump pliers DIN 5231

chrome vanadium, 31 Cr V3, box-joint, burner hole, teeth induction hardened, finger protection, oil-hardened, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 05 83	300	380	6

VDE pliers, coating-insulated, head insulated

Combination pliers DIN ISO 5244 VDE

working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 02 63	185	290	1
21 02 64	205	385	1

Side cutters DIN ISO 5749 VDE

working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 03 01	160	270	1
21 03 02	180	330	1

Long chain nose pliers DIN ISO 5754 VDE

straight, working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 02 66	160	170	1
21 02 67	200	225	1

Long chain nose pliers DIN ISO 5745 VDE

angled nose, working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 02 97	200	210	1

Plan grip pliers VDE

working head insulated, made of special alloy steel, long, flat, plain gripping jaws, round edges, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 02 98	200	215	1

Short flat nose pliers DIN ISO 5745 VDE

working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 02 99	160	200	1

Long chain nose pliers DIN ISO 5745 VDE

working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 03 00	160	205	1

Wire stripping pliers DIN 5232 VDE

working head insulated, 2-coloured coating-insulation - inside yellow/outside red



⚠ 1000 V IEC 60900:2004

Art. No.	length	weight	PU
21 02 65	160	180	1